



ENERG Y UA EHEPΓИЯ · ενεργεια IE IA



GREENMASTER - HP-4-16-15

35 °C































ENERG IJA енергия · ενεργεια




GREENMASTER - HP-4-16-15

∭∭ 55 °C





















Product fiche

Supplier's name:	Air-		
Model:	GreenMaste		
Temperature application	35	55	°C
Declared load profile for water heating			
Seasonal space heating energy efficiency class, average climate:	A++	A++	
Water heating energy efficiency class, average climate:			
Rated heat output, average climate:	55	55	kW
Annual energy consumption for space heating, average climate	25272	29202	kWh
Annual electricity consumption for water heating, average climate			kWh
Seasonal space heating energy efficiency, average climate:	177	153	%
Water heating energy efficiency, average climate:			%
Sound power level LWA indoors	67	67	dB
Rated heat output, cold climate:	55	55	kW
Rated heat output, warm climate:	54	54	kW
Annual energy consumption for space heating, cold climate	28485	33116	kWh
Annual electricity consumption for water heating, cold climate			kWh
Annual energy consumption for space heating, warm climate	15711	18381	kWh
Annual electricity consumption for water heating, warm climate			kWh
Seasonal space heating energy efficiency, cold climate:	187	161	%
Water heating energy efficiency, cold climate:			%
Seasonal space heating energy efficiency, warm climate:	181	154	%
Water heating energy efficiency, warm climate:			%
Sound power level LWA outdoors	-	_	dB

Data for package fiche

Controller class	[
Controler contribution to efficiency		%	
Seasonal space heating energy efficiency of package, average climate:	179	155	%
Seasonal space heating energy efficiency class for package, average climate:	A+++	A+++	%
Seasonal space heating energy efficiency of package, cold climate:	189	163	%
Seasonal space heating energy efficiency of package, warm climate:	183	156	%

Model(s):			GreenM	aster - HP-4-16-15				
Type of heat source/sink:		Exhau		ust air-to-water			_	
Low-temperature heat pump:			No					
Equipped with supplementary heater:			No				_	
Heat pump combination heater:		No No No Average mperature (55 °C)			C:4	- ~®		
Climate condition:		Average	\boldsymbol{A} H		ווכי	6		
Temperature application:			Medium	temperature (55 °C)				
Applied standards: EN14825, EN14511 ar	nd EN12102							
				Seasonal space heating ene	ergy			
Rated heat output	Prated	55,0	kW	efficiency		η_{s}	153	%
Declared capacity for part load at outdoor temperature Tj			Declared coefficient of performance for part load at outdoor temperature Tj					
Tj = -7 °C	Pdh	36,1	kW	Tj = -7 °C		COPd	3,33	kW
Tj = +2 °C	Pdh	29,7	kW	Tj = +2 °C		COPd	4,31	kW
Tj = +7 °C	Pdh	19,1	kW	Tj = +7 °C		COPd	4,86	kW
Tj = +12 °C	Pdh	8,7	kW	Tj = +12 °C		COPd	5,89	kW
Tj = biv	Pdh	36,1	kW	Tj = biv		COPd	3,70	kW
Tj = TOL	Pdh	35,6	kW	Tj = TOL		COPd	3,22	kW
Tj = -15 °C (if TOL < -20 °C)	Pdh		kW	Tj = -15 °C (if TOL < -20 °C)		COPd	·	kW
Bivalent temperature	T _{biv}	-1	°C	Operation limit temperature	e	TOL	-10	°C
Cycling interval capacity for heating	Pcych		kW	Cycling interval efficiency		COPcvc		_
Degradation co-efficient	Cdh	0,96	-	Heating water operating lim		WTOL	65	°C
Power consumption in modes other than active	modo			Supplementary heater				
Off mode	P _{OFF}	0,012	kW	Rated heat output		Psup	0,0	kW
Thermostat-off mode	P _{TO}	0,16	kW	·	<u> </u>		<u> </u>	I.
Standby mode	P _{SB}	0,01	kW	Type of energy input -				
Crankcase heater mode	P _{CK}	0,09	kW	7,7	Type of energy input			
Other items								
Capacity control		variable		Rated air flow rate, outdoor	rs		4320	m³/h
Sound power level, indoors/outdoors	L _{WA}	67/-	dB	Rated brine or water flow ra	ate			
Annual energy consumption	Q _{HE}	29202	kWh	outdoor heat exchanger	utc,		-	m³/h
For heat pump combination heater:								
Declared load profile				Water heating energy efficie	iency	η_{wh}		%
Daily electricity consumption	Q_{elec}		kWh	Daily fuel consumption		Q_{fuel}		kWh
Annual electricity consumption	AEC		kWh	Annual fuel consumption		AFC		GJ
Approved by:								

Air-Site AB - Elementvägen 1 - 437 36 Lindome - Sweden

Contact details